

SLANA PRO - MODEL: AES3NC

Surface Mounted Luminaires

WAC LIGHTING


PROJECT :

TYPE :

Product Image



Line Drawing



Product Description

The Slana Pro surface mounted tube lights are more decorative in building lighting, using ceiling and suspension installation. The exquisite and meticulous appearance and structural design, excellent optical performance, and flexible humanized accessories can bring users a perfect light environment experience. The lighting fixtures have angle adjustment function and are suitable for functional lighting in public high spaces.

Product Features

- Body Material: Die cast aluminum end caps and lamp bodies
- Optical System: Lens
- Finish: Static electricity powder coating
- Adjustable Angle: Horizontal 355 °; vertical ±25 °
- Accessories: /
- Certification: CCC
- IP Rating: IP65
- Insulation Level: Class I
- Operating Temperature: -20℃~50℃

Product Specifications

- LED Type: COB
- LED Power: 13W (Max)
- Source Lm: 3000K 1560lm;4000K 1690lm
- LED Lifetime: >50000h-L70 /B10-Ta25℃(LM-80/TM-21)
- CCT/CRI: 3000K / 4000K , Ra80
- SDCM: 3 SDCM
- Input: 220V/AC , 50/60Hz
- Dimming: ON-OFF
- Net Weight: 1.0Kg without packing

Order Model

Model	Comment	Power (W)	LEDs (quantity)	Max Lumens (lm)	Control Systems	Beam	CCT	Reflector	Finish
AES3N	C Ceiling Mounted	13 13(Max)	COB	690	EL ON-OFF 220V AC Power Supply DL 0-10V Dimming 220V AC Power Supply	1 13 ° 2 20 ° 3 30 ° 4 40 °	30 3000K 40 4000K	B Black S Specular	WT White

Example : AES3NC-13EL130BWT

SLANA PRO - MODEL: AES3NC

Surface Mounted Luminaires


WAC LIGHTING

PROJECT :


TYPE :

Accessories


LIGHT DISTRIBUTION@3000K LUMINAIRE DATA




MODEL :	AES3NC-13EL130SWT
BEAM ANGLE :	13 °
POWER :	14.9W
LUMENS :	799.4 lm
CBCP :	/
EFFICACY :	53.4 lm /W



MODEL :	AES3NC-13EL230SWT
BEAM ANGLE :	20 °
POWER :	15.2W
LUMENS :	906 lm
CBCP :	/
EFFICACY :	59.6 lm /W



MODEL :	AES3NC-13EL330SWT
BEAM ANGLE :	30 °
POWER :	15.26W
LUMENS :	911 lm
CBCP :	/
EFFICACY :	59.7 lm /W



MODEL :	AES3NC-13EL430SWT
BEAM ANGLE :	40 °
POWER :	15.1W
LUMENS :	856 lm
CBCP :	/
EFFICACY :	56.8 lm /W

SLANA PRO - MODEL: AES3SC

Surface Mounted Luminaires

WAC LIGHTING


PROJECT :

TYPE :

Product Image



Line Drawing



Product Description

The Slana Pro surface mounted tube lights are more decorative in building lighting, using ceiling and suspension installation. The exquisite and meticulous appearance and structural design, excellent optical performance, and flexible humanized accessories can bring users a perfect light environment experience. The lighting fixtures have angle adjustment function and are suitable for functional lighting in public high spaces.

Product Features

- Body Material: Die cast aluminum end caps and lamp bodies
- Optical System: Lens
- Finish: Static electricity powder coating
- Adjustable Angle: Horizontal 355 °; vertical ± 25 °
- Accessories: /
- Certification: CCC
- IP Rating: IP65
- Insulation Level: Class I
- Operating Temperature: -20℃~50℃

Product Specifications

- LED Type: COB
- LED Power: 18W (Max)
- Source Lm: 3000K 2160lm;4000K 2340lm
- LED Lifetime: >50000h-L70 /B10-Ta25℃(LM-80/TM-21)
- CCT/CRI: 3000K / 4000K , Ra80
- SDCM: 3 SDCM
- Input: 220V/AC , 50/60Hz
- Dimming: ON-OFF/0-10V
- Net Weight: 1.0Kg without packing

Order Model

Model	Comment	Power (W)	LEDs (quantity)	Max Lumens (lm)	Control Systems	Beam	CCT	Reflector	Finish
AES3S	C Ceiling Mounted	18 18(Max)	COB	1500	EL ON-OFF	1 19 °	30 3000K 40 4000K	B Black S Specular	WT White
					220V AC Power Supply	2 26 °			
					DL 0-10V Dimming	3 38 °			
					220V AC Power Supply	5 52 °			

Example : AES3SC-18EL130BWT

SLANA PRO - MODEL: AES3SC

Surface Mounted Luminaires





WAC LIGHTING

PROJECT :

TYPE :

Accessories

LIGHT DISTRIBUTION@3000K LUMINAIRE DATA

	MODEL : BEAM ANGLE : POWER : LUMENS : CBCP : EFFICACY :	AES3SC-18EL130BWT 19 ° 19.1W 1599 lm / 83.5 lm /W		MODEL : BEAM ANGLE : POWER : LUMENS : CBCP : EFFICACY :	AES3SC-18EL230BWT 26 ° 19.1W 1656 lm / 88.8 lm /W
	MODEL : BEAM ANGLE : POWER : LUMENS : CBCP : EFFICACY :	AES3SC-18EL330BWT 38 ° 19.1W 1699 lm / 88.9 lm /W		MODEL : BEAM ANGLE : POWER : LUMENS : CBCP : EFFICACY :	AES3SC-18EL530BWT 52 ° 19.2W 1592 lm / 82.8 lm /W

SLANA PRO - MODEL: AES3MC

Surface Mounted Luminaires

WAC LIGHTING


PROJECT :

TYPE :

Product Image



Line Drawing



Product Description

The Slana Pro surface mounted tube lights are more decorative in building lighting, using ceiling and suspension installation. The exquisite and meticulous appearance and structural design, excellent optical performance, and flexible humanized accessories can bring users a perfect light environment experience. The lighting fixtures have angle adjustment function and are suitable for functional lighting in public high spaces.

Product Features

- Body Material: Die cast aluminum end caps and lamp bodies
- Optical System: Lens
- Finish: Static electricity powder coating
- Adjustable Angle: Horizontal 355 °; vertical ± 25 °
- Accessories: /
- Certification: CCC
- IP Rating: IP65
- Insulation Level: Class I
- Operating Temperature: -20℃~50℃

Product Specifications

- LED Type: COB
- LED Power: 33W (Max)
- Source Lm: 3000K 4180lm ; 4000K 4318lm
- LED Lifetime: >50000h-L70 /B10-Ta25℃(LM-80/TM-21)
- CCT/CRI: 3000K / 4000K , Ra80
- SDCM: 3 SDCM
- Input: 220V/AC , 50/60Hz
- Dimming: ON-OFF/0-10V (Conduct compatibility testing in advance)
- Net Weight: 2.5Kg without packing

Order Model

Model	Comment	Power (W)	LEDs (quantity)	Max Lumens (lm)	Control Systems	Beam	CCT	Reflector	Finish
AES3M	C Ceiling Mounted	33 33(Max)	COB	2500	EL ON-OFF				
					220V AC Power Supply	1 19 °	30		
					DL 0-10V Dimming	2 26 °	3000K	B Black	WT
					220V AC Power Supply	3 38 °	40	S Specular	White
						5 52 °	4000K		

Example : AES3MC-33EL130BWT

SLANA PRO - MODEL: AES3MC

Surface Mounted Luminaires


WAC LIGHTING

PROJECT :


TYPE :

Accessories


LIGHT DISTRIBUTION@3000K LUMINAIRE DATA




MODEL :	AES3MC-33EL130SWT
BEAM ANGLE :	19 °
POWER :	37.2W
LUMENS :	3550 lm
CBCP :	/
EFFICACY :	95.4 lm /W



MODEL :	AES3MC-33EL230SWT
BEAM ANGLE :	26 °
POWER :	37.3W
LUMENS :	3498 lm
CBCP :	/
EFFICACY :	93.6 lm /W



MODEL :	AES3MC-33EL330SWT
BEAM ANGLE :	38 °
POWER :	37.5W
LUMENS :	3694 lm
CBCP :	/
EFFICACY :	98.6 lm /W



MODEL :	AES3MC-33EL530SWT
BEAM ANGLE :	52 °
POWER :	37.1W
LUMENS :	3329 lm
CBCP :	/
EFFICACY :	89.7 lm /W