


2" Square Recessed Tunable Downlight

PROJECT :

TYPE:



Product Description

ULTRA Tunable Square recessed adjustable color temperature downlight, through a unique Angle adjustment, taking into account the function of downlighting and adjustment (one light multi-purpose). The whole lamp sealing design ensures that there is no light leakage during the adjustment process, the lamp adopts the modular design, the on-site lamp can be freely disassembled and replaced the reflector and the lamp body, so as to achieve a variety of specifications and the free switching of light mode, and the perfect integration of the ceiling after installation. In terms of optics, it adopts a new hidden light technology and is equipped with a color temperature control function, which is mainly suitable for indoor places such as hotels, villas and commercial Spaces.

Product Features

- Body Material: Aluminum alloy die-cast lamp body
- Optical System: Lens + anti-glare reflector
- Finish: Electrostatic powder spraying
- Adjustable Angle: Vertical adjustment 0-30 °, horizontal adjustment 0-360 °
- Accessories: As attached
- Certification: CCC
- IP Rating: IP20
- Insulation Level: Class II
- Operating Temperature: -20°C~40°C

Product Specifications

- Cut-out: 60*60mm
- Ceiling Thickness: 5mm~15mm
- Shielding Angle: 35°
- LED Type: COB
- Source Lm: 700lm
- LED Lifetime: >36000h-L70/B10-Ta25°C(LM-80/TM-2 1)
- CCT/ SDCM: 2700K-6000K Adjustment, CRI≥90
- Input: 220V AC / 50 Hz
- Dimming: DALI(must be tested for compatibility with the project site system in advance)
- Net Weight: 0.12Kg without packing

Order Model





Model	Size	Trim	LED	Driver	Beam	CCT	Reflector	Finish
ADLN	2	5	LM07	A DALI	2 24°	CC 2700K-6000K	B Black	WT White
Downlight	2"	Rectangular	COB 7W	N No Driver	3 36°	(Tunable)	S Specular	BK Black
N series		Trim			5 50°			

Example: ADLN25-LM07A2CCSWT

2" Square Recessed Tunable Downlight




PROJECT :

TYPE:

ALENS-08-BEL Striped glass lens		ALENS-08-BSL Soft glass lens		ALENS-08-FR Frosted glass lens		ALENS-08-HCL Honeycomb	
-------------------------------------------	-----------------------------------------------------------------------------------	----------------------------------------	-----------------------------------------------------------------------------------	------------------------------------------	-------------------------------------------------------------------------------------	----------------------------------	-------------------------------------------------------------------------------------

Note: Up to one optical accessory can be added, which is not delivered with accessories and needs to be ordered separately.


LIGHT DISTRIBUTION@3000K LUMINAIRE DATA

	MODEL: ADLN25-LM07A2CCSWT		MODEL: ADLN25-LM07A3CCSWT
BEAM ANGLE: 24°		BEAM ANGLE: 36°	
POWER: 8.4W		POWER: 8.4W	
LUMENS: 395lm		LUMENS: 380lm	
CBCP: 1992cd		CBCP: 769cd	
EFFICACY: 47lm/W		EFFICACY: 45lm/W	
	MODEL: ADLN25-LM07A5CCSWT		
BEAM ANGLE: 50°			
POWER: 8.4W			
LUMENS: 348lm			
CBCP: 499cd			
EFFICACY: 41lm/W			

3" Square Recessed Tunable Downlight

PROJECT :

TYPE:



Product Description

ULTRA Tunable series LED Square recessed adjustable color temperature downlight, through a unique Angle adjustment, taking into account the function of downlighting and adjustment (one light multi-purpose). The whole lamp sealing design ensures that there is no light leakage during the adjustment process, the lamp adopts the modular design, the on-site lamp can be freely disassembled and replaced the reflector and the lamp body, so as to achieve a variety of specifications and the free switching of light mode, and the perfect integration of the ceiling after installation. In terms of optics, it adopts a new hidden light technology and is equipped with a color temperature control function, which is mainly suitable for indoor places such as hotels, villas and commercial Spaces.

Product Features

- Body Material: Aluminum alloy die-cast lamp body
- Optical System: Lens + anti-glare reflector
- Finish: Electrostatic powder spraying
- Adjustable Angle: Vertical adjustment 0-30 °, horizontal adjustment 0-360 °
- Accessories: As attached
- Certification: CCC
- IP Rating: IP20
- Insulation Level: Class II
- Operating Temperature: -20°C~40°C

Product Specifications

- Cut-out: 79*79mm
- Ceiling Thickness: 5mm~25mm
- Shielding Angle: 35°
- LED Type: COB
- Source Lm: 1300lm
- LED Lifetime: >36000h-L70/B10-Ta25°C(LM-80/TM-2 1)
- CCT/ SDCM: 2700K-6000K Adjustment, CRI≥90
- Input: 220V AC / 50 Hz
- Dimming: DALI(must be tested for compatibility with the project site system in advance)
- Net Weight: 0.45Kg without packing

Order Model

Model	Size	Trim	LED	Driver	Beam	CCT	Reflector	Finish
ADLN	3	5	LM13	A DALI	1 18°	CC 2700K-6000K	B Black	WT White
Downlight	3"	Rectangular	COB 13W	N No Driver	2 24°	(Tunable)	S Specular	BK Black
N series		Trim			3 36°			
					5 50°			

Example：ADLN35-LM13A2CCSWT

Note: 18° factory default with endless honeycomb grille


3" Square Recessed Tunable Downlight

PROJECT :


TYPE:

ALENS-11-BEL Striped glass lens		ALENS-11-BSL-ULTRA Soft glass lens		ALENS-11-FR Frosted glass lens		ALENS-11-HCL-ULTRA Honeycomb	
-------------------------------------------	-----------------------------------------------------------------------------------	----------------------------------------------	-----------------------------------------------------------------------------------	------------------------------------------	-------------------------------------------------------------------------------------	----------------------------------------	-------------------------------------------------------------------------------------


Note: Up to one optical accessory can be added, which is not delivered with accessories and needs to be ordered separately.




MODEL:	ADLN35-LM13A1CCSWT
BEAM ANGLE:	18°
POWER:	16W
LUMENS:	688lm
CBCP:	4588cd
EFFICACY:	43lm/W



MODEL:	ADLN35-LM13A2CCSWT
BEAM ANGLE:	28°
POWER:	16W
LUMENS:	1042lm
CBCP:	3976cd
EFFICACY:	65lm/W



MODEL:	ADLN35-LM13A3CCSWT
BEAM ANGLE:	36°
POWER:	16W
LUMENS:	923lm
CBCP:	2309cd
EFFICACY:	58lm/W




MODEL:	ADLN35-LM13A5CCSWT
BEAM ANGLE:	50°
POWER:	16W
LUMENS:	740lm
CBCP:	902cd
EFFICACY:	46lm/W

4" Square Recessed Tunable Downlight

PROJECT :

TYPE:



Product Description

ULTRA Tunable series LED Square recessed adjustable color temperature downlight, through a unique Angle adjustment, taking into account the function of downlighting and adjustment (one light multi-purpose). The whole lamp sealing design ensures that there is no light leakage during the adjustment process, the lamp adopts the modular design, the on-site lamp can be freely disassembled and replaced the reflector and the lamp body, so as to achieve a variety of specifications and the free switching of light mode, and the perfect integration of the ceiling after installation. In terms of optics, it adopts a new hidden light technology and is equipped with a color temperature control function, which is mainly suitable for indoor places such as hotels, villas and commercial Spaces.

Product Features

- Body Material: Aluminum alloy die-cast lamp body
- Optical System: Lens + anti-glare reflector
- Finish: Electrostatic powder spraying
- Adjustable Angle: Vertical adjustment 0-30 °, horizontal adjustment 0-360 °
- Accessories: As attached
- Certification: CCC
- IP Rating: IP20
- Insulation Level: Class II
- Operating Temperature: -20°C~40°C

Product Specifications

- Cut-out: 100*100mm
- Ceiling Thickness: 5mm~25mm
- Shielding Angle: 35°
- LED Type: COB
- Source Lm: 3000lm
- LED Lifetime: >36000h-L70/B10-Ta25°C(LM-80/TM-2 1)
- CCT/ SDCM: 2700K-6000K Adjustment, CRI≥90
- Input: 220V AC / 50 Hz
- Dimming: No dimming/DALI(must be tested for compatibility with the project site system in advance)
- Net Weight: 0.8Kg without packing

Order Model

Model	Size	Trim	LED	Driver	Beam	CCT	Reflector	Finish
ADLN Downlight N series	4 4"	5 Rectangular Trim	LM25 COB 25W	A DALI N No Driver	1 18°	CC 2700K-6000K (Tunable)	B Black S Specular	WT White
					2 28°			BK Black
					3 36°			
					5 50°			

Example: ADLN45-LM25A2CCSWT


4" Square Recessed Tunable Downlight

PROJECT :

TYPE:


ALENS-16-BEL-C

Striped glass lens




ALENS-16-BSL-SW

Soft glass lens







ALENS-16-HCL-ULTRA

Honeycomb



Note: Up to one optical accessory can be added, which is not delivered with accessories and needs to be ordered separately.

	<div>MODEL:ADLN45-LM25A1CCSWT</div> <div>BEAM ANGLE:18°</div> <div>POWER:27W</div> <div>LUMENS:1672lm</div> <div>CBCP:11139cd</div> <div>EFFICACY:62lm/W</div>		<div>MODEL:ADLN45-LM25A2CCSWT</div> <div>BEAM ANGLE:28°</div> <div>POWER:27W</div> <div>LUMENS:1821lm</div> <div>CBCP:8382cd</div> <div>EFFICACY:67lm/W</div>
	<div>MODEL:ADLN45-LM25A3CCSWT</div> <div>BEAM ANGLE:36°</div> <div>POWER:27W</div> <div>LUMENS:1502lm</div> <div>CBCP:2921cd</div> <div>EFFICACY:56lm/W</div>		<div>MODEL:ADLN45-LM25A5CCSWT</div> <div>BEAM ANGLE:50°</div> <div>POWER:27W</div> <div>LUMENS:1469lm</div> <div>CBCP:2161cd</div> <div>EFFICACY:54 lm/W</div>