

ULTRA TUNABLE - MODEL:ADLN33
3" Round Narrow Recessed Downlight

WAC LIGHTING


PROJECT:

TYPE:

Product Image



Line Drawing



Product Description

ULTRA circular narrow side embedded downlight , the total height is only 55mm, through glass sealing, Can be used for anti fog or low ceiling space. the lighting fixtures adopt modular design, on site lighting fixtures can be freely disassembled and replaced with reflectors and lamp bodies, so as to achieve free switching of various specifications and light output methods, perfect integration with ceiling after installation, the optical aspect adopts a new stealth technology, mainly suitable for indoor spaces such as hotels, villas, and commercial spaces.

Product Features

- Body Material: Aluminum alloy die-casting
- Optical System: Lens+ SUBOROSA optical system
- Finish: Static electricity powder coating
- Adjustable Angle: 0-360° horizontal rotation vertical non adjustable
- Accessories: As attached
- Certification: CCC/CE
- IP Rating: IP20(Light source cavity IP44)
- Insulation Level: Class II
- Operating Temperature: -20°C~40°C

Product Specifications

- Cut-out: Ø78
- Ceiling 5mm~25mm Thickness
- Shielding Angle: 35°
- LED Type: COB
- Source Lm:
 - 2700K: 8W 682lm; 7W 758lm; 10W 1080lm; 13W 1404lm
 - 3000K: 8W 720lm; 7W 800lm; 10W 1150lm; 13W 1495lm
 - 3500K: 8W 752lm; 7W 835lm; 10W 1195lm; 13W 1554lm
 - 4000K: 8W 765lm; 7W 850lm; 10W 1210lm; 13W 1573lm
 - 5000K: 8W 774lm; 7W 860lm; 10W 1220lm; 13W 1586lm
- LED Lifetime: >36000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 2700K/3000K/3500K/4000K/5000K
CRI≥90
- SDCM: 3 SDCM
- Input: 220V~240V AC / 50Hz
- Dimming: ON-OFF/0-10V/DALI
- Net Weight: 0.3Kg without packing

Order Model

Model	Size	Trim	LED	Driver	Beam	CCT	Reflector	Finish
ADLN Downlight N series	3 3"	3 Round trim	LM07 COB 7W	E on-off	N 13°	27 2700K	B Black	WT White
			LM10 COB 10W	D 0-10V	1 18°	30 3000K	S Specular	BK Black
			LM13 COB 13W	Dimming	2 28°	35 3500K		
			LM13 COB 13W		3 36°	40 4000K		
					N No Driver	5 50°		
			A DALI					

Example: ADLN33-LM07E230SWT

Note: 13 °and 18 ° are factory default with honeycomb grilles.

WAC Lighting
www.waclighting.com (US)
www.waclighting.net (International)

Headquarters
44 Harbor Park Drive • Port Washington, NY
Phone (516) 515.5000 • Fax (516) 515.5050

WAC Lighting(Shanghai)
14,Lane 299, Bi Sheng Road, Shanghai 201204,China
Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598

ULTRA TUNABLE - MODEL:ADLN33
3" Round Narrow Recessed Downlight

WAC LIGHTING

PROJECT:









TYPE:

ALENS-12-HCL-ULTRA
Honeycomb



Note: 13 °and 18 ° are factory default with honeycomb grilles, Honeycomb installed on the back of the reflector.

LIGHT DISTRIBUTION@3000K LUMINAIRE DATA








	MODEL:ADLN33-LM07EN30SWT BEAM ANGLE:13° POWER:9W LUMENS:533lm CBCP:5684cd EFFICACY:59 lm/W		MODEL:ADLN33-LM10EN30SWT BEAM ANGLE:13° POWER:11W LUMENS:643 lm CBCP:7056 cd EFFICACY:58 lm/W
	MODEL:ADLN33-LM13EN30SWT BEAM ANGLE:13° POWER:15W LUMENS:820 lm CBCP:8174 cd EFFICACY:55 lm/W		MODEL:ADLN33-LM07E5130SWT BEAM ANGLE:18° POWER:9W LUMENS:585 lm CBCP:4163 cd EFFICACY:65 lm/W
	MODEL:ADLN33-LM10E130SWT BEAM ANGLE:18° POWER:11W LUMENS:714lm CBCP:5090cd EFFICACY:56 lm/W		MODEL:ADLN33-LM13E130SWT BEAM ANGLE:18° POWER:15W LUMENS:935 lm CBCP:6848cd EFFICACY:62 lm/W
	MODEL:ADLN33-LM07E230SWT BEAM ANGLE:28° POWER:9W LUMENS:641 lm CBCP:2885cd EFFICACY:71 lm/W		MODEL:ADLN33-LM10E230SWT BEAM ANGLE:28° POWER:11W LUMENS:790 lm CBCP:3511cd EFFICACY:72 lm/W

ULTRA TUNABLE - MODEL:ADLN33
3" Round Narrow Recessed Downlight

WAC LIGHTING

PROJECT:

TYPE:

	MODEL: ADLN33-LM13E230SWT		MODEL: ADLN33-LM07E330SWT
BEAM ANGLE: 28°	BEAM ANGLE: 36°	POWER: 15W	POWER: 9W
LUMENS: 1035lm	LUMENS: 643lm	CBCP: 4511cd	CBCP: 1497cd
EFFICACY: 69lm/W	EFFICACY: 71lm/W		
	MODEL: ADLN33-LM10E330SWT		MODEL: ADLN33-LM13E330SWT
BEAM ANGLE: 36°	BEAM ANGLE: 36°	POWER: 11W	POWER: 15W
LUMENS: 804lm	LUMENS: 1024lm	CBCP: 1857cd	CBCP: 2375cd
EFFICACY: 73lm/W	EFFICACY: 68lm/W		
	MODEL: ADLN33-LM07E530SWT		MODEL: ADLN33-LM10E530SWT
BEAM ANGLE: 50°	BEAM ANGLE: 50°	POWER: 9W	POWER: 11W
LUMENS: 425lm	LUMENS: 532lm	CBCP: 574cd	CBCP: 717cd
EFFICACY: 47lm/W	EFFICACY: 48lm/W		
	MODEL: ADLN33-LM13E530SWT		
BEAM ANGLE: 50°		POWER: 15W	
LUMENS: 677lm		CBCP: 914cd	
EFFICACY: 45lm/W			

ULTRA TUNABLE - MODEL:ADLN43
4" Round Narrow Recessed Downlight

WAC LIGHTING


PROJECT:

TYPE:

Product Image



Line Drawing



Product Description

ULTRA circular narrow side embedded downlight , the total height is only 55mm, through glass sealing, Can be used for anti fog or low ceiling space. the lighting fixtures adopt modular design, on site lighting fixtures can be freely disassembled and replaced with reflectors and lamp bodies, so as to achieve free switching of various specifications and light output methods, perfect integration with ceiling after installation, the optical aspect adopts a new stealth technology, mainly suitable for indoor spaces such as hotels, villas, and commercial spaces.

Product Features

- Body Material: Aluminum alloy die-casting
- Optical System: Lens+ SUBOROSA optical system
- Finish: Static electricity powder coating
- Adjustable Angle: 0-360° horizontal rotation vertical non adjustable
- Accessories: As attached
- Certification: CCC/CE
- IP Rating: IP20(Light source cavity IP44)
- Insulation Level: Class II
- Operating Temperature: -20°C~40°C

Product Specifications

- Cut-out: Ø100
- Ceiling 5mm~25mm Thickness
- Shielding Angle: 35°
- LED Type: COB
- Source Lm:
2700K: 8W 682lm; 13W 1530lm; 18W 2065lm; 25W 2755lm
3000K: 8W 720lm; 13W 1645lm; 18W 2220lm; 25W 2960lm
3500K: 8W 752lm; 13W 1680lm; 18W 2270lm; 25W 3025lm
4000K: 8W 765lm; 13W 1770lm; 18W 2390lm; 25W 3185lm
5000K: 8W 774lm; 13W 1780lm; 18W 2405lm; 25W 3205lm
- LED Lifetime: >36000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 2700K/3000K/3500K/4000K/5000K,Ra90
- SDCM: 3 SDCM
- Input: 220V~240V AC / 50Hz
- Dimming: ON-OFF/0-10V/DALI
- Net Weight: 0.5Kg without packing

Order Model

Model	Size	Trim	LED		Driver	Beam		CCT		Reflector		Finish	
ADLN Downlight N series	4 4"	3 Round trim	LM08	COB 8W	E on-off	S	8°	27	2700K	B	Black	WT	White
			LM13	COB 13W	D 0-10V	N	13°	30	3000K	S	Specular	BK	Black
			LM18	COB 18W	Dimming	1	19°	35	3500K				
			LM25	COB 25W		2	28°	40	4000K				
			LM25	COB 25W		N No Driver	3	36°	50	5000K			
					A DALI	5	50°						

Example: ADLN43-LM18E230SWT

ULTRA TUNABLE - MODEL:ADLN43

4" Round Narrow Recessed Downlight

WAC LIGHTING

PROJECT:

TYPE:

ALENS-16-HCL-ULTRA
Honeycomb



Note: "S"/"N"/"1"are factory default with honeycomb grilles, other angles need to be ordered separately.

LIGHT DISTRIBUTION@3000K LUMINAIRE DATA


	MODEL: ADLN43-LM13EN30SWT	BEAM ANGLE: 13°	POWER: 15W	LUMENS: 969lm	CBCP: 8386cd	EFFICACY: 65lm/W
	MODEL: ADLN43-LM18EN30SWT	BEAM ANGLE: 13°	POWER: 21W	LUMENS: 1309lm	CBCP: 11333cd	EFFICACY: 62lm/W
	MODEL: ADLN43-LM25EN30SWT	BEAM ANGLE: 13°	POWER: 29W	LUMENS: 1716lm	CBCP: 14853cd	EFFICACY: 59lm/W
	MODEL: ADLN43-LM25EN30SWT	BEAM ANGLE: 19°	POWER: 15W	LUMENS: 1135lm	CBCP: 5812cd	EFFICACY: 76lm/W
	MODEL: ADLN43-LM18E130SWT	BEAM ANGLE: 19°	POWER: 21W	LUMENS: 1533lm	CBCP: 7854cd	EFFICACY: 73lm/W
	MODEL: ADLN43-LM25E130SWT	BEAM ANGLE: 19°	POWER: 29W	LUMENS: 2009lm	CBCP: 10294cd	EFFICACY: 69lm/W
	MODEL: ADLN43-LM13E230SWT	BEAM ANGLE: 28°	POWER: 15W	LUMENS: 1327lm	CBCP: 5429cd	EFFICACY: 88lm/W
	MODEL: ADLN43-LM18E230SWT	BEAM ANGLE: 28°	POWER: 21W	LUMENS: 1793lm	CBCP: 7336cd	EFFICACY: 85 lm/W

ULTRA TUNABLE - MODEL:ADLN43
4" Round Narrow Recessed Downlight


WAC LIGHTING

PROJECT:


TYPE:




MODEL:	ADLN43-LM25E230SWT
BEAM ANGLE:	28°
POWER:	29W
LUMENS:	2351lm
CBCP:	9615cd
EFFICACY:	81lm/W




MODEL:	ADLN43-LM13E330SWT
BEAM ANGLE:	36°
POWER:	15W
LUMENS:	1268lm
CBCP:	2722cd
EFFICACY:	85lm/W




MODEL:	ADLN43-LM18E330SWT
BEAM ANGLE:	36°
POWER:	21W
LUMENS:	1714lm
CBCP:	3679cd
EFFICACY:	82lm/W




MODEL:	ADLN43-LM25E330SWT
BEAM ANGLE:	36°
POWER:	29W
LUMENS:	2246lm
CBCP:	4821cd
EFFICACY:	77lm/W




MODEL:	ADLN43-LM13E530SWT
BEAM ANGLE:	50°
POWER:	15W
LUMENS:	1237lm
CBCP:	1843cd
EFFICACY:	82lm/W



MODEL:	ADLN43-LM18E530SWT
BEAM ANGLE:	50°
POWER:	21W
LUMENS:	1671lm
CBCP:	2490cd
EFFICACY:	80lm/W



MODEL:	ADLN43-LM25E530SWT
BEAM ANGLE:	50°
POWER:	29W
LUMENS:	2190lm
CBCP:	3263cd
EFFICACY:	76lm/W



MODEL:	ADLN43-LM08E30SWT
BEAM ANGLE:	8°
POWER:	10W
LUMENS:	375lm
CBCP:	9280cd
EFFICACY:	38lm/W