

FALCON ROUND - MODEL: ATL71S

W Track Luminaires


PROJECT:

TYPE:

Product Image



Line Drawing



Product Description

FALCON ROUND series LED track lights are suitable for W three-circuit tracks. The lamp structure is slim and three-dimensional, using WAC's leading SUBROSA hidden light technology, and has a 35° anti-glare angle for ultimate anti-glare effect. The lamp has a built-in high-quality LED constant current electrical appliance, and can choose advanced wireless dimming control functions. At the same time, it provides a variety of different light distribution forms and can be equipped with various optical accessories to meet different application environment requirements. It is widely used in museums, art galleries, science museums and other places.

Product Features

- Body Material: Aluminum alloy die-casting, PC optical components
- Optical System: Lenses and SUBROSA Reflectors
- Surface Finishing: Static electricity powder coating, Black (BK), White (WT)
- Adjustable Angle: Horizontal: 0-355° tilt, Vertical: 0~90° tilt
- Accessories: Up to three optical accessories can be added; Each type can only be installed with one at most
- Certification: CCC/CE
- IP Rating: IP20
- Insulation Level: Class I
- Operating Temperature: -20°C~40°C

Product Specifications

- LED Type: HP LED
- LED Power: 3W/8W/12W
- Source Lm: 3000K: 250LM(3W)/700LM(8W)/875LM(12W); 4000K: 265LM(3W)/740LM(8W)/925LM(12W)
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 3000K/4000K, Ra90/Ra97,
- SDCM: 3 SDCM
- Input: 220V~240V AC / 50Hz
- Dimming: On-boarding(10%-100%)/ Wireless(WAC system is required)/ DALI/0-10V
- Net Weight: 0.6Kg without packing

Order Model

Model	LED		Dimming	Beam	CRI	CCT	Finish
ATL71S FALCON ROUND	LD03	LED 3W	O On-boarding D 0-10V B Wireless A DALI	V 4°	9 90 A 97	30 3000K 40 4000K	WT White BK Black
	LD08 LED 8W LD12 LED 12W			S 7°			
				1 14°			
				2 20°			
				3 30°			
				4 40°			
				G 20*55° E 10*30°			
				ATL71S			

WAC Lighting
www.waclighting.com (US)
www.waclighting.net (International)

Headquarters
44 Harbor Park Drive • Port Washington, NY
Phone (516) 515.5000 • Fax (516) 515.5050

WAC Lighting(Shanghai)
14,Lane 299, Bi Sheng Road, Shanghai 201204,China
Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598

WAC Lighting reserves the right to periodically design and update products.2024-01-24

FALCON ROUND - MODEL: ATL71S

W Track Luminaires

WAC LIGHTING

PROJECT:

TYPE:

Example: ATL71SLD08-O2930WT


Note: When the light emitting surface of the luminaire is parallel to the illuminated surface, 20*55° and 10*30° indicate transverse stretched light spots.

Accessories


Class 1 Accessories	ALENS-TL71S-“typ.” Vari-optic Lens (t=3mm)		Model Note: “typ.” Representative: beam diffusion lens in various angles “10D/20D/30D/40D/55D” or stretched lens “1060D”; Example: LENS-TL71S-10D	
	ALENS-TL71S-FR Frosted Glass Lens	ALENS-TL71S-BSL Flexible Glass Lenses	ALENS-TL71S-BEL Stretched Glass Lenses	ALENS-TL71S-HCM Anti-glare Bee Grille
Class 2 Accessories	ALENS-TL71S-WW Wall Washer Assembly			
Class 3 Accessories	ALENS-TL71S-BD Four-leaf Blindfold			

Note: Up to three optical accessories can be added, with a maximum of one per type of accessory; please consult WAC for beam angles after adding vari-optic lenses.


LIGHT DISTRIBUTION@3000K LUMINAIRE DATA




MODEL:	ATL71SLD08-OS930
BEAM ANGLE:	7°
POWER:	10W
LUMENS:	271lm
CBCP:	10443cd
EFFICACY:	27lm/W




MODEL:	ATL71SLD12-OS930
BEAM ANGLE:	7°
POWER:	16W
LUMENS:	380lm
CBCP:	14621cd
EFFICACY:	24lm/W




MODEL:	ATL71SLD08-O1930
BEAM ANGLE:	14°
POWER:	10W
LUMENS:	433lm
CBCP:	4519cd
EFFICACY:	43lm/W



MODEL:	ATL71SLD12-O1930
BEAM ANGLE:	14°
POWER:	16W
LUMENS:	606lm
CBCP:	6327cd
EFFICACY:	38lm/W



MODEL:	ATL71SLD08-O2930
BEAM ANGLE:	20°
POWER:	10W
LUMENS:	577lm
CBCP:	4201cd
EFFICACY:	58lm/W




MODEL:	ATL71SLD12-O2930
BEAM ANGLE:	20°
POWER:	16W
LUMENS:	808lm
CBCP:	5881cd
EFFICACY:	51lm/W

FALCON ROUND - MODEL: ATL71S

W Track Luminaires

PROJECT:

TYPE:



MODEL: ATL71SLD08-O3930


BEAM ANGLE: 30°

POWER: 10W

LUMENS: 569lm

CBCP: 2169cd

EFFICACY: 57lm/W



MODEL: ATL71SLD12-O3930


BEAM ANGLE: 30°

POWER: 16W

LUMENS: 797lm

CBCP: 3036cd

EFFICACY: 50lm/W



MODEL: ATL71SLD08-O4930


BEAM ANGLE: 40°

POWER: 10W

LUMENS: 564lm

CBCP: 1187cd

EFFICACY: 56lm/W



MODEL: ATL71SLD12-O4930


BEAM ANGLE: 40°

POWER: 16W

LUMENS: 508lm

CBCP: 1150cd

EFFICACY: 51lm/W



MODEL: ATL71SLD08-OG930


BEAM ANGLE: 20*55°

POWER: 10W

LUMENS: 500lm

CBCP: 1461cd

EFFICACY: 50lm/W



MODEL: ATL71SLD12-OG930


BEAM ANGLE: 20*55°

POWER: 16W

LUMENS: 789lm

CBCP: 1662cd

EFFICACY: 49lm/W



MODEL: ATL71SLD08-OE930


BEAM ANGLE: 10*30°

POWER: 10W

LUMENS: 579lm

CBCP: 5064cd

EFFICACY: 58lm/W



MODEL: ATL71SLD12-OE930


BEAM ANGLE: 10*30°

POWER: 16W

LUMENS: 811lm

CBCP: 7590cd

EFFICACY: 51lm/W



MODEL: ATL71SLD03-OV930

BEAM ANGLE: 4°

POWER: 4W

LUMENS: 149lm

CBCP: 9901cd

EFFICACY: 37lm/W

FALCON ROUND - MODEL: ATL72S

W Track Luminaires


PROJECT:

TYPE:

Product Image



Line Drawing



Product Description

FALCON ROUND series LED track lights are suitable for W three-circuit tracks. The lamp structure is slim and three-dimensional, using WAC's leading SUBROSA hidden light technology, and has a 35° anti-glare angle for ultimate anti-glare effect. The lamp has a built-in high-quality LED constant current electrical appliance, and can choose advanced wireless dimming control functions. At the same time, it provides a variety of different light distribution forms and can be equipped with various optical accessories to meet different application environment requirements. It is widely used in museums, art galleries, science museums and other places.

Product Features

- Body Material: Aluminum alloy die-casting, PC optical components
- Optical System: Lenses and SUBROSA Reflectors
- Surface Finishing: Static electricity powder coating, Black (BK), White (WT)
- Adjustable Angle: Horizontal: 0-355° tilt, Vertical: 0~90° tilt
- Accessories: Up to three optical accessories can be added; Each type can only be installed with one at most
- Certification: CCC/CE
- IP Rating: IP20
- Insulation Level: Class I
- Operating Temperature: -20°C~40°C

Product Specifications

- LED Type: HP LED
- LED Power: 12W/18W/27W
- Source Lm: 3000K: 1000LM(12W)/1575LM(18W)/2125LM(27W)
4000K: 1060LM(12W)/1665LM(18W)/2245LM(27W)
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 3000K/4000K, Ra90/Ra97,
- SDCM: 3 SDCM
- Input: 220V~240V AC / 50Hz
- Dimming: On-boarding(10%-100%)/ Wireless(WAC system is required)/ DALI/0-10V
- Net Weight: 0.9Kg without packing

Order Model

Model	LED	Dimming	Beam	CRI	CCT	Finish
ATL72S FALCON ROUND	LD12 LED 12W	O On-boarding D 0-10V B Wireless A DALI	V 4°	9 90 A 97	30 3000K 40 4000K	WT White BK Black
	LD18 LED 18W LD27 LED 27W		S 7°			
			1 14°			
			2 20°			
			3 30°			
			4 40°			
			G 20*55°			
			E 10*30°			
ATL72S	LD18	0	2	9	30	WT

WAC Lighting
www.waclighting.com (US)
www.waclighting.net (International)

Headquarters
44 Harbor Park Drive • Port Washington, NY
Phone (516) 515.5000 • Fax (516) 515.5050

WAC Lighting(Shanghai)
14,Lane 299, Bi Sheng Road, Shanghai 201204,China
Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598

FALCON ROUND - MODEL: ATL72S

W Track Luminaires

WAC LIGHTING

PROJECT:

TYPE:

Example: ATL72SLD18-O2930WT


Note: When the light emitting surface of the luminaire is parallel to the illuminated surface, 20*55° and 10*30° indicate transverse stretched light spots.

Accessories

Class 2 Accessories	ALENS-TL72S-“typ.” Vari-optic lens (t=3mm)		Model Note: “typ.” Representative: beam diffusion lens in various angles “10D/20D/30D/40D/55D” or stretched lens “1060D”; Example: LENS-TL72S-10D	
	ALENS-TL72S-FR Frosted Glass Lens	ALENS-TL72S-BSL Flexible Glass Lenses	ALENS-TL72S-BEL Stretched Glass Lenses	ALENS-TL72S-HCM Anti-glare Bee Grille
Class 2 Accessories	ALENS-TL72S-WW Wall Washer Assembly			
Class 3 Accessories	ALENS-TL72S-BD Four-leaf Blindfold			

Note: Up to three optical accessories can be added, with a maximum of one per type of accessory; please consult WAC for beam angles after adding Vari-optic lenses.

LIGHT DISTRIBUTION@3000K LUMINAIRE DATA




FALCON ROUND - MODEL: ATL72S


W Track Luminaires

PROJECT:


TYPE:




MODEL:	ATL72SLD18-O3930
BEAM ANGLE:	30°
POWER:	21W
LUMENS:	1058lm
CBCP:	3879cd
EFFICACY:	50lm/W




MODEL:	ATL72SLD27-O3930
BEAM ANGLE:	30°
POWER:	31W
LUMENS:	1481lm
CBCP:	5431cd
EFFICACY:	48lm/W




MODEL:	ATL72SLD18-O4930
BEAM ANGLE:	40°
POWER:	21W
LUMENS:	908lm
CBCP:	2488cd
EFFICACY:	43lm/W




MODEL:	ATL72SLD27-O4930
BEAM ANGLE:	40°
POWER:	31W
LUMENS:	1271lm
CBCP:	3484cd
EFFICACY:	41lm/W




MODEL:	ATL72SLD18-OG930
BEAM ANGLE:	20*55°
POWER:	21W
LUMENS:	971lm
CBCP:	3066cd
EFFICACY:	46lm/W




MODEL:	ATL72SLD27-OG930
BEAM ANGLE:	20*55°
POWER:	31W
LUMENS:	1357lm
CBCP:	4286cd
EFFICACY:	44lm/W



MODEL:	ATL72SLD18-O-E930
BEAM ANGLE:	10*30°
POWER:	21W
LUMENS:	1003lm
CBCP:	6914cd
EFFICACY:	48lm/W



MODEL:	ATL72SLD27-O-E930
BEAM ANGLE:	10*30°
POWER:	31W
LUMENS:	1404lm
CBCP:	9673cd
EFFICACY:	45lm/W



MODEL:	ATL72SLD12-OV930
BEAM ANGLE:	4°
POWER:	16W
LUMENS:	685lm
CBCP:	40811cd
EFFICACY:	43lm/W

FALCON ROUND - MODEL: ATL73S

WAC LIGHTING

W Track Luminaires


PROJECT:

TYPE:

Product Image



Line Drawing



Product Description

FALCON ROUND series LED track lights are suitable for W three-circuit tracks. The lamp structure is slim and three-dimensional, using WAC's leading SUBROSA hidden light technology, and has a 35° anti-glare angle for ultimate anti-glare effect. The lamp has a built-in high-quality LED constant current electrical appliance, and can choose advanced wireless dimming control functions. At the same time, it provides a variety of different light distribution forms and can be equipped with various optical accessories to meet different application environment requirements. It is widely used in museums, art galleries, science museums and other places.

Product Features

- Body Material: Aluminum alloy die-casting, PC optical components
- Optical System: Lenses and SUBROSA Reflectors
- Surface Finishing: Static electricity powder coating, Black (BK), White (WT)
- Adjustable Angle: Horizontal: 0-365° tilt, Vertical: 0~90° tilt
- Accessories: Up to three optical accessories can be added; Each type can only be installed with one at most
- Certification: CCC/CE
- IP Rating: IP20
- Insulation Level: Class I
- Operating Temperature: -20°C~40°C

Product Specifications

- LED Type: HP LED
- LED Power: 27W/32W/42W
- Source Lm: 3000K: 2125LM(27W)/2800LM(32W)/2960LM(42W)
4000K: 2245LM(27W)/3500LM(32W)/3700LM(42W)
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 3000K/4000K, Ra90/Ra97,
- SDCM: 3 SDCM
- Input: 220V~240V AC / 50Hz
- Dimming: On-boarding(10%-100%)/ Wireless(WAC system is required)/ DALI/0-10V
- Net Weight: 1.3Kg without packing

Order Model

Model	LED		Dimming	Beam	CRI	CCT	Finish
ATL73S FALCON ROUND	LD27	LED 27W	O On-boarding D 0-10V B Wireless A DALI	V 4°	9 90 A 97	30 3000K 40 4000K	WT White BK Black
	LD32 LED 32W LD43 LED 43W			S 7°			
				1 14°			
				2 20°			
				3 30°			
				4 40°			
				G 20*55° E 10*30°			
				ATL73S			

FALCON ROUND - MODEL: ATL73S

W Track Luminaires

PROJECT:

WAC

TYPE:

Example: ATL73SLD32-O2930WT


Note: When the light emitting surface of the luminaire is parallel to the illuminated surface, 20*55° and 10*30° indicate transverse stretched light spots.

Accessories


Class 1 Accessories	ALENS-TL73S-“typ.” Vari-optic lens (t=3mm)		Model Note: “typ.” Representative: beam diffusion lens in various angles “10D/20D/30D/40D/55D” or stretched lens “1060D”; Example: LENS-TL73S-10D	
	ALENS-TL73S-FR Frosted Glass Lens	ALENS-TL73S-BSL Flexible Glass Lenses	ALENS-TL73S-BEL Stretched Glass Lenses	ALENS-TL73S-HCM Anti-glare Bee Grille
Class 2 Accessories	ALENS-TL73S-WW Wall Washer Assembly			
Class 3 Accessories	ALENS-TL73S-BD Four-leaf Blindfold			

Note: Up to three optical accessories can be added, with a maximum of one per type of accessory; please consult WAC for beam angles after adding vari-optic lenses.


LIGHT DISTRIBUTION@3000K LUMINAIRE DATA




MODEL:	ATL73SLD32-OS930
BEAM ANGLE:	7°
POWER:	36W
LUMENS:	953lm
CBCP:	32610cd
EFFICACY:	26lm/W




MODEL:	ATL73SLD43-OS930
BEAM ANGLE:	7°
POWER:	48W
LUMENS:	1209lm
CBCP:	41383cd
EFFICACY:	25lm/W




MODEL:	ATL73SLD32-O1930
BEAM ANGLE:	14°
POWER:	36W
LUMENS:	1570lm
CBCP:	15736cd
EFFICACY:	44lm/W



MODEL:	ATL73SLD48-O1930
BEAM ANGLE:	14°
POWER:	48W
LUMENS:	1992lm
CBCP:	19969cd
EFFICACY:	42lm/W



MODEL:	ATL73SLD32-O2930
BEAM ANGLE:	20°
POWER:	36W
LUMENS:	2045lm
CBCP:	14394cd
EFFICACY:	57lm/W



MODEL:	ATL73SLD43-O2930
BEAM ANGLE:	20°
POWER:	48W
LUMENS:	2596lm
CBCP:	18266cd
EFFICACY:	54lm/W

WAC Lighting
www.waclighting.com (US)
www.waclighting.net (International)

Headquarters
44 Harbor Park Drive • Port Washington, NY
Phone (516) 515.5000 • Fax (516) 515.5050

WAC Lighting(Shanghai)
14,Lane 299, Bi Sheng Road, Shanghai 201204,China
Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598


FALCON ROUND - MODEL: ATL73S

W Track Luminaires


PROJECT:

WAC


TYPE:




MODEL:	ATL73SLD32-O3930
BEAM ANGLE:	30°
POWER:	36W
LUMENS:	1808lm
CBCP:	6913cd
EFFICACY:	50lm/W




MODEL:	ATL73SLD43-O3930
BEAM ANGLE:	30°
POWER:	48W
LUMENS:	2295lm
CBCP:	8773cd
EFFICACY:	48lm/W




MODEL:	ATL73SLD32-O4930
BEAM ANGLE:	40°
POWER:	36W
LUMENS:	1621lm
CBCP:	4385cd
EFFICACY:	45lm/W




MODEL:	ATL73SLD43-O4930
BEAM ANGLE:	40°
POWER:	48W
LUMENS:	2057lm
CBCP:	5565cd
EFFICACY:	43lm/W




MODEL:	ATL73SLD32-OG930
BEAM ANGLE:	20*55°
POWER:	36W
LUMENS:	1821lm
CBCP:	5490cd
EFFICACY:	51lm/W




MODEL:	ATL73SLD43-OG930
BEAM ANGLE:	20*55°
POWER:	48W
LUMENS:	2311lm
CBCP:	6967cd
EFFICACY:	48lm/W



MODEL:	ATL73SLD32-OE930
BEAM ANGLE:	10*30°
POWER:	36W
LUMENS:	1655lm
CBCP:	11107cd
EFFICACY:	46lm/W



MODEL:	ATL73SLD43-OE930
BEAM ANGLE:	10*30°
POWER:	48W
LUMENS:	2100lm
CBCP:	14095cd
EFFICACY:	44lm/W



MODEL:	ATL73SLD27-OV930
BEAM ANGLE:	4°
POWER:	31W
LUMENS:	1480lm
CBCP:	93734cd
EFFICACY:	48lm/W