## **VOLO- MODEL: AOC4N**

# WAC LIGHTING

Responsible Lighting®


## **Linear Luminaires**

Project Name:	Туре:	
	•	

**Line Drawing** 

Product Image





#### **Product Description**

The LIGNE III features a specialized lens or polarized optical system combined with an optimized LED arrangement, delivering uniform wall illumination with no dark spots or glare. It offers high-efficiency heat dissipation, low energy consumption, and a soft anti-glare lighting effect. With a DC 24V input, fixtures can be connected end-to-end for continuous installation. Ideal for recessed linear wall-grazing applications in offices, exhibition halls, hotels, and commercial public areas.

#### **Product Features**

Body Materials:
Aluminum die-casting lamp body

• Optical System: Lens

• Finishes: Electrostatic powder coating

Objection Direction:

Accessory/Bracket: see atta hment

Certification: CCC
IP Rating: IP20
Insulation Level: Class III
Operating Temperature: -20℃ - 50℃

#### **Product Specifications**

•Shading Angle: /

•**LED Type**: SMD LED

•Source Lm: 1m:5000lm@3000K; 1m:5600lm@4000K

•**LED Lifetime**: > 50,000h-L70 /B10-Ta25°C(LM-80/TM-21)

•CCT/CRI: 2700K/3000K/4000K, Ra90

•SDCM: 3 SDCM •Input: 24V DC

•Dimming: User-supplied dimming module(Matching

tests must be done with the project site

systems)

•Net Weight: Approx. 0.6Kg, without packaging

### **Order Model**

Model	Diameter (mm)	Power (W)	Driver	Beam	ССТ	Finish
OC4N	<b>02</b> 244	<b>05</b> 05W	N No Driver	W Wall Wash	<b>27</b> 2700K	WT White
	<b>05</b> 484	<b>10</b> 10W			<b>30</b> 3000K	<b>BK</b> Black
	<b>10</b> 964	<b>20</b> 20W			<b>40</b> 4000K	

Example: AOC4N-1020NW30WT

Note: Maximum continuous connection length: 5m.

## **VOLO-** MODEL: AOC4N

# **WAC LIGHTING**

Responsible Lighting®

	•		•
L	inear	Lumin	aires

Project Name:	Туре:	

#### Accessory

Model	ltem	Dimensions
AOC3N-AB001	Adjust Bracket	11 13
AOC3N-PCCT002F	Female connector	21—————————————————————————————————————
AOC3N-PCCT002M	Male connector	20-180-10
AOC4N-CG100WT AOC4N-CG100BK	960mm Cover	240 10 29
AOC4N-CG050WT AOC4N-CG050BK	480mm Cover	480
AOC4N-CG025WT AOC4N-CG025BK	240mm Cover	000000000000000000000000000000000000000
AOC4N-CB100WT AOC4N-CB100BK	960mm Cover	240 7 14
AOC4N-CB050WT AOC4N-CB050BK	480mm Cover	- 480 - 960
AOC4N-CB025WT AOC4N-CB025BK	240mm Cover	000000000000000000000000000000000000000
AOC4N-HC100BK	960mm	240
AOC4N-HC050BK	480mm	960
AOC4N-HC025BK	240mm	300