

ELANA- MODEL: ADLG21

2" Narrow Trim Recessed Downlight

PROJECT :


WAC

TYPE :

Product Image



Line Drawing



Product Description

The ELANA series LED narrow edge embedded downlight integrates perfectly with the ceiling after installation. Good anti-glare performance and color consistency control, with comfortable light output effect, mainly suitable for indoor places such as hotels and clubs.-

Product Features

- Body Material: Aluminum alloy die-casting
- Optical System: Lens+ Anti-glare reflector
Reflector surface treatment:
B Black
W White
S Black Mirror
T Black staircase
H White staircase
- Finish: Static electricity powder
- Adjustable Angle: /
- Accessories: As attached
- Certification: CCC/CE
- IP Rating: IP20
- Insulation Level: Class II
- Operating Temperature: -20°C~40°C

Product Specifications

- Cut-out: Ø 55mm
- Ceiling Thickness 5mm~25mm
- Shielding Angle: 35°
- LED Type: COB
- Source Lm:
2700K: 4W 540lm ; 7W 758lm;
3000K: 4W 557lm ; 7W 780lm;
3500K: 4W 578lm ; 7W 810lm;
4000K: 4W 589lm ; 7W 825lm;
5000K: 4W 594lm ; 7W 832lm;
- LED Lifetime: >36000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 2700K/3000K/3500K/4000K/5000K , CRI≥90
- Input: 220V~240V AC / 50Hz
- Dimming: No diming/ 0-10V (Must conduct compatibility testing with the project site system in advance)
- Net Weight: 0.11Kg without packing

Order Model

Model	Size	Trim	LED	Driver	Beam	CCT	Reflector	Finish
ADLG Downlight G series	2 2"	1 Round Trim	LM04 COB 4W	E On-Off	1 15°	27 2700K	B Black	WT
			LM07 COB 7W	D 0-10V Dimming	2 24°	30 3000K	W White	White
					3 36°	35 3500K	S Specular	BK
			LM07 COB 7W	N No Driver	5 50°	40 4000K 50 5000K	T Black Step H White Step	Black

Example : ADLG21-LM07E130SWT

Note: The 15 °and 24° factory default comes with an rimless honeycomb grille.

ELANA- MODEL: ADLG21

2" Narrow Trim Recessed Downlight

PROJECT :

WAC


TYPE :

LENS-11-HCL-ELANA

Honeycomb



LIGHT DISTRIBUTION@3000K LUMINAIRE DATA



MODEL : ADLG21-LM04E130BWT


BEAM ANGLE : 15°

POWER : 5.4W

LUMENS : 215lm

CBCP : 2014cd

EFFICACY : 39lm/W



MODEL : ADLG21-LM07E130BWT


BEAM ANGLE : 15°

POWER : 8W

LUMENS : 306lm

CBCP : 2867cd

EFFICACY : 38lm/W



MODEL : ADLG21-LM04E230BWT


BEAM ANGLE : 24°

POWER : 5.4W

LUMENS : 249lm

CBCP : 1532cd

EFFICACY : 45lm/W



MODEL : ADLG21-LM07E230BWT


BEAM ANGLE : 24°

POWER : 8W

LUMENS : 355lm

CBCP : 2181cd

EFFICACY : 44lm/W



MODEL : ADLG21-LM04E330BWT


BEAM ANGLE : 36°

POWER : 5.4W

LUMENS : 314lm

CBCP : 778cd

EFFICACY : 57lm/W



MODEL : ADLG21-LM07E330BWT


BEAM ANGLE : 36°

POWER : 8W

LUMENS : 447lm

CBCP : 1104cd

EFFICACY : 55lm/W



MODEL : ADLG21-LM04E530BWT


BEAM ANGLE : 50°

POWER : 5.4W

LUMENS : 342lm

CBCP : 509cd

EFFICACY : 62lm/W



MODEL : ADLG21-LM07E530BWT

BEAM ANGLE : 50°

POWER : 8W

LUMENS : 486lm

CBCP : 725cd

EFFICACY : 60lm/W

ELANA - MODEL: ADLG31

3" Narrow Trim Recessed Downlight


PROJECT :

WAC
TYPE :

Product Image



Line Drawing



Product Description

The ELANA series LED narrow edge embedded downlight integrates perfectly with the ceiling after installation. Good anti-glare performance and color consistency control, with comfortable light output effect, mainly suitable for indoor places such as hotels and clubs.-

Product Features

- Body Material: Aluminum alloy die-casting
- Optical System: Lens+ Anti-glare reflector
Reflector surface treatment:
B Black
W White
S Black Mirror
T Black staircase
H White staircase
- Finish: Static electricity powder
- Adjustable Angle: /
- Accessories: As attached
- Certification: CCC/CE
- IP Rating: IP20
- Insulation Level: Class II
- Operating Temperature: -20°C~40°C

Product Specifications

- Cut-out: Ø 75mm
- Ceiling Thickness 5mm~25mm
- Shielding Angle: 35°
- LED Type: COB
- Source Lm:
2700K: 7W 758lm; 10W 1080lm; 13W 1404lm
3000K: 7W 800lm; 10W 1150lm; 13W 1495lm
3500K: 7W 835lm; 10W 1195lm; 13W 1554lm
4000K: 7W 850lm; 10W 1210lm; 13W 1573lm
5000K: 7W 860lm; 10W 1220lm; 13W 1586lm
- LED Lifetime: >36000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 2700K/3000K/3500K/4000K/5000K , CRI≥90
- Input: 220V~240V AC / 50Hz
- Dimming: No diming/ 0-10V (Must conduct compatibility testing with the project site system in advance)
- Net Weight: 0.24Kg without packing

Order Model

Model	Size	Trim	LED	Driver	Beam	CCT	Reflector	Finish
ADLG Downlight G series	3 3"	1 Round Trim	LM07 COB7W	E On-Off	1 15°	27 2700K	B Black	WT
			LM10 COB 10W	D 0-10V	2 24°	30 3000K	W White	White
			LM13 COB 13W	Dimming	3 36°	35 3500K	S Specular	BK
			LM13 COB 13W	N No Driver	5 50°	40 4000K 50 5000K	T Black Step H White Step	Black

Example : ADLG31-LM07E130SWT

Note: The 15 °and 24° factory default comes with an rimless honeycomb grille.

ELANA - MODEL: ADLG31

3" Narrow Trim Recessed Downlight


PROJECT :




LENS-12-HCL-ELANA

Honeycomb


LIGHT DISTRIBUTION@3000K LUMINAIRE DATA




MODEL :	ADLG31-LM07E130BWT
BEAM ANGLE :	15°
POWER :	8W
LUMENS :	340lm
CBCP :	3781cd
EFFICACY :	42lm/W




MODEL :	ADLG31-LM10E130BWT
BEAM ANGLE :	15°
POWER :	11W
LUMENS :	456lm
CBCP :	5076cd
EFFICACY :	41lm/W




MODEL :	ADLG31-LM13E130BWT
BEAM ANGLE :	24°
POWER :	15W
LUMENS :	615lm
CBCP :	6839cd
EFFICACY :	41lm/W




MODEL :	ADLG31-LM07E230BWT
BEAM ANGLE :	24°
POWER :	8W
LUMENS :	416lm
CBCP :	2223cd
EFFICACY :	52lm/W




MODEL :	ADLG31-LM10E230BWT
BEAM ANGLE :	24°
POWER :	11W
LUMENS :	558lm
CBCP :	2985cd
EFFICACY :	50lm/W



MODEL :	ADLG31-LM13E230BWT
BEAM ANGLE :	24°
POWER :	15W
LUMENS :	753lm
CBCP :	4021cd
EFFICACY :	50lm/W



MODEL :	ADLG31-LM07E330BWT
BEAM ANGLE :	36°
POWER :	8W
LUMENS :	604lm
CBCP :	1272cd
EFFICACY :	75lm/W




MODEL :	ADLG31-LM10E330BWT
BEAM ANGLE :	36°
POWER :	11W
LUMENS :	809lm
CBCP :	1703cd
EFFICACY :	73lm/W


ELANA - MODEL: ADLG31

3" Narrow Trim Recessed Downlight


PROJECT :




MODEL :	ADLG31-LM13E330BWT
BEAM ANGLE :	36°
POWER :	15W
LUMENS :	1090lm
CBCP :	2285cd
EFFICACY :	72lm/W



MODEL :	ADLG31-LM07E530BWT
BEAM ANGLE :	50°
POWER :	8W
LUMENS :	573lm
CBCP :	773cd
EFFICACY :	71lm/W



MODEL :	ADLG31-LM10E530BWT
BEAM ANGLE :	50°
POWER :	11W
LUMENS :	770lm
CBCP :	1038cd
EFFICACY :	70lm /W



MODEL :	ADLG31-LM13E530BWT
BEAM ANGLE :	50°
POWER :	15W
LUMENS :	1038lm
CBCP :	1398cd
EFFICACY :	69lm /W