

ULTRA - MODEL: ASLN32

Ceiling Mount Luminaires




PROJECT:

TYPE:

Product Image



Line Drawing



Product Description

The ULTRA series LED circular exposed tube lamp adopts a modular design, and on-site lamps can be freely disassembled and replaced with reflectors and lamp bodies, thereby achieving free switching of various specifications and lighting methods. In terms of optics, a brand new hidden light technology is adopted, which has good anti glare performance and color consistency control, and has a comfortable lighting effect. It is mainly suitable for indoor places such as hotels, villas, and commercial spaces.

Product Features

- Body Material: Aluminum alloy die-casting body
- Optical System: Lens+ Anti glare reflector
- Finish: Static electricity powder coating
- Projection direction: /
- Accessories/Brackets: See accessory list
- Certification: CCC
- IP Rating: IP20
- Insulation Level: Class II
- Operating Temperature: -20°C~40°C

Product Specifications

- Shielding Angle: 35°
- LED Type: COB
- Source Lm: 3000K 1000LM,4000K 1100LM;
2700K: 8W 682 lm; 7W 758 lm; 10W 1080 lm; 13W 1404 lm
3000K: 8W 720 lm; 7W 800 lm; 10W 1150 lm; 13W 1495 lm
3500K: 8W 752 lm; 7W 835 lm; 10W 1195 lm; 13W 1554 lm
4000K: 8W 765 lm; 7W 850 lm; 10W 1210 lm; 13W 1573 lm
5000K: 8W 774 lm; 7W 860 lm; 10W 1220 lm; 13W 1586 lm
- LED Lifetime: >36000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 2700K/3000K/3500K/4000K/5000K, CRI≥90
- Input: 220V AC /50Hz
- Dimming: No Dimming/0-10V(Must conduct compatibility testing with the project site in advance)
- Net Weight: 0.36Kg without packing

Order Model

Model	Size	Trim	LED		Driver		Beam		CCT		Reflector		Finish
ASLN	3	2	LM08	COB 8W	E	On-Off	S	8°	27	2700K	B	Black	WT
Surface	3"	Ronnd	LM07	COB 7W	D	0-10V	N	13°	30	3000K	S	Specular	White
Mounted		Trimless	LM10	COB 10W		Dimming	1	18°	35	3500K			BK
Downlight			LM13	COB 13W			2	28°	40	4000K			Black
N series							3	36°	50	5000K			
							5	50°					

Example: ASLN32-LM07EN30SWT

Note: 8 °, 13 °, and 18 °are factory default with honeycomb grilles.

ULTRA - MODEL: ASLN32

Ceiling Mount Luminaires











PROJECT:

TYPE:

Accessory			
ALENS-11-BEL Striped glass lenses		ALENS-11-BSL-ULTRA Soft glass lenses	
		ALENS-11-FR Frosted glass lenses	
		ALENS-11-HCL-ULTRA Borderless honeycomb grille	

Note: Up to one optical accessory can be added; Among them, 8 °, 13 °, and 18 °are factory default with borderless honeycomb grilles.

LIGHT DISTRIBUTION@3000K LUMINAIRE DATA


	MODEL: ASLN32-LM07E-N30SWT BEAM ANGLE: 13 ° POWER: 9W LUMENS: 466 lm CBCP: 5571cd EFFICACY: 52 lm/W		MODEL: ASLN32-LM10E-N30SWT BEAM ANGLE: 13 ° POWER: 11W LUMENS: 520 lm CBCP: 6220cd EFFICACY: 47 lm/W
	MODEL: ASLN32-LM13EN30SWT BEAM ANGLE: 13 ° POWER: 16W LUMENS: 676 lm CBCP: 8086cd EFFICACY: 42 lm/W		MODEL: ASLN32-LM07E130SWT BEAM ANGLE: 18 ° POWER: 9W LUMENS: 721lm CBCP: 5316cd EFFICACY: 80 lm/W
	MODEL: ASLN32-LM10E130SWT BEAM ANGLE: 18 ° POWER: 11W LUMENS: 817 lm CBCP: 6028cd EFFICACY: 74 lm/W		MODEL: ASLN32-LM13E130SWT BEAM ANGLE: 18 ° POWER: 16W LUMENS: 1062 lm CBCP: 7836cd EFFICACY: 66 lm/W
	MODEL: ASLN32-LM07E230SWT BEAM ANGLE: 28 ° POWER: 9W LUMENS: 715 lm CBCP: 3052cd EFFICACY: 79 lm/W		MODEL: ASLN32-LM10E230SWT BEAM ANGLE: 28 ° POWER: 11W LUMENS: 796 lm CBCP: 3396cd EFFICACY: 72 lm/W

ULTRA - MODEL: ASLN32
Ceiling Mount Luminaires




PROJECT:


TYPE:




MODEL:	ASLN32-LM13E230SWT
BEAM ANGLE:	28 °
POWER:	15W
LUMENS:	1035 lm
CBCP:	4511cd
EFFICACY:	69 lm/W




MODEL:	ASLN32-LM07E330SWT
BEAM ANGLE:	36 °
POWER:	9W
LUMENS:	643 lm
CBCP:	1497cd
EFFICACY:	71 lm/W




MODEL:	ASLN32-LM10E330SWT
BEAM ANGLE:	36 °
POWER:	11W
LUMENS:	804 lm
CBCP:	1857cd
EFFICACY:	73 lm/W




MODEL:	ASLN32-LM13E330SWT
BEAM ANGLE:	36 °
POWER:	15W
LUMENS:	1024lm
CBCP:	2375cd
EFFICACY:	68 lm/W




MODEL:	ASLN32-LM07E530SWT
BEAM ANGLE:	50 °
POWER:	9W
LUMENS:	425 lm
CBCP:	574cd
EFFICACY:	47 lm/W



MODEL:	ASLN32-LM10E530SWT
BEAM ANGLE:	50 °
POWER:	119W
LUMENS:	532 lm
CBCP:	717cd
EFFICACY:	48 lm/W



MODEL:	ASLN32-LM13E530SWT
BEAM ANGLE:	50 °
POWER:	15W
LUMENS:	677 lm
CBCP:	914cd
EFFICACY:	45 lm/W



MODEL:	ASLN32-LM08E30SWT
BEAM ANGLE:	8 °
POWER:	10W
LUMENS:	375lm
CBCP:	9280cd
EFFICACY:	38 lm/W