

PLANA PRO - MODEL: ASDL22

Ceiling Mount Luminaires

WAC


PROJECT:

TYPE:

Product Image



Line Drawing



Product Description

The PLANA PRO surface mounted tube light is exquisite and simple, with precise light distribution. It adopts SUBROSA hidden light technology and has the ultimate anti glare effect. Mainly suitable for hotels and commercial public spaces.

Product Features

- Body Material: Aluminum alloy extruded lamp body
- Optical System: Lens+ SUBROSA optical system
- Finish: Static electricity powder coating
- Projection direction: /
- Accessories/Brackets: /
- Certification: CCC
- IP Rating: IP20
- Insulation Level: Class I
- Operating Temperature: -20°C~40°C

Product Specifications

- Shielding Angle: 35°
- LED Type: HIGH POWER LED
- Source Lm: 800 LM/8W 3000K
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 2700K/3000K/3500K/4000K/5000K, Ra90
- SDCM: 3 SDCM
- Input: 220V-240V AC /50Hz
- Dimming: No dimming/0-10V (must be matched with the project site system in advance Testing)
- Net Weight: 0.4Kg without packing

Order Model

Model	Size	Trim	LED	Driver	Beam	CCT	Reflector	Finish
ASDL	2	2	LD08	E ON-OFF	1 15°	27 2700K	B Black	WT White
Surface	2"	Round	HP LED 8W	D 0-10V	2 24°	30 3000K	S Specular	BK Black
Mount		Trimless		Dimming	3 36°	35 3500K		
Downlight					4 48°	40 4000K		
						50 5000K		

Example: ASDL22-LD08D230SWT

Accessory

/

PLANA PRO - MODEL: ASDL22


Ceiling Mount Luminaires




PROJECT:

TYPE:


LIGHT DISTRIBUTION@3000K LUMINAIRE DATA




MODEL:	ASDL22-LD08D130SWT
BEAM ANGLE:	15°
POWER:	10 W
LUMENS:	521 lm
CBCP:	4577 cd
EFFICACY:	52 lm/W



MODEL:	ASDL22-LD08D230SWT
BEAM ANGLE:	24°
POWER:	10 W
LUMENS:	556 lm
CBCP:	3004 cd
EFFICACY:	55 lm/W



MODEL:	ASDL22-LD08D330SWT
BEAM ANGLE:	36°
POWER:	10 W
LUMENS:	493 lm
CBCP:	1182 cd
EFFICACY:	49 lm/W



MODEL:	ASDL22-LD08D430SWT
BEAM ANGLE:	48°
POWER:	10 W
LUMENS:	464 lm
CBCP:	726 cd
EFFICACY:	46 lm/W