

ELANA - MODEL: ADDG25
2" Square Narrow Side Recessed Downlight

WAC


PROJECT:

TYPE:

Product Image



Line Drawing



Product Description

The ELANA series of LED recessed downlights with square narrow edges are the perfect combination of downlighting and angle adjustment. Good anti-glare performance and color consistency control, with comfortable light effect, mainly suitable for indoor places such as hotels and clubs.

Product Features

- Body Material: Aluminum alloy die-casting
- Optical System: Lens+ Anti-glare reflector
Reflector surface treatment:
 - B Black
 - W White
 - S Black Mirror
 - T Black Step
 - H White Step
- Finish: Static electricity powder coating
- Adjustable Angle: Vertical 0°~25° , Aclinic 0°~355°
- Accessories: As attached
- Certification: CCC
- IP Rating: IP20
- Insulation Level: Class II
- Operating Temperature: -20°C~40°C

Product Specifications

- Cut-out: 55*55mm
- Ceiling Thickness: 5mm~15mm
- Shielding Angle: 35°
- LED Type: COB
- Source Lm:
 - 2700K: 4W 540LM; 7W 758LM;
 - 3000K: 4W 557LM; 7W 780LM;
 - 3500K: 4W 578LM; 7W 810LM;
 - 4000K: 4W 589LM; 7W 825LM;
 - 5000K: 4W 594LM; 7W 832LM;
- LED Lifetime: >36000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 2700K/ 3000K/3500K/4000K/5000K, Ra90
- SDCM: 3 SDCM (4000K 5SDCM)
- Input: 220V~240V AC / 50Hz
- Dimming: On-off / 0-10V /DALI
- Net Weight: 0.11Kg without packing

Order Model

Model	Size	Trim	LED	Driver	Beam	CCT	Reflector	Finish
ADDG Downlight Directional G series	2 2"	5 Rectangular Trim	LM04 COB 4W	E ON-OFF D 0-10V Dimming	1 15°	27 2700K	B Black	WT White BK Black
			LM07 COB 7W		2 24°	30 3000K	W White	
					3 36°	35 3500K	S Specular	
			LM07 COB 7W	N NO DRIVER	5 50°	40 4000K 50 5000K	T Black Step H White Step	

Example: ADDG25-LM07E130SWT

Note: 15° and 24° have honeycomb by default, and there is no honeycomb at other angles

ELANA - MODEL: ADDG25

2" Square Narrow Side Recessed Downlight

WAC

PROJECT:

TYPE:


LENS-11-HCL-ELANA

Honeycomb



Note: 15° and 24° have honeycomb by default, and there is no honeycomb at other angles.

LIGHT DISTRIBUTION@3000K LUMINAIRE DATA



MODEL: ADDG25-LM04E130BWT


BEAM ANGLE: 15°

POWER: 5.5W

LUMENS: 233lm

CBCP: 2177cd

EFFICACY: 40lm/W



MODEL: ADDG25-LM07E130BWT


BEAM ANGLE: 15°

POWER: 8W

LUMENS: 322lm

CBCP: 3134cd

EFFICACY: 40lm/W



MODEL: ADDG25-LM04E230BWT


BEAM ANGLE: 24°

POWER: 5.5W

LUMENS: 221lm

CBCP: 1354cd

EFFICACY: 40lm/W



MODEL: ADDG25-LM07E230BWT


BEAM ANGLE: 24°

POWER: 8W

LUMENS: 318lm

CBCP: 1949cd

EFFICACY: 39lm/W



MODEL: ADDG25-LM04E330BWT


BEAM ANGLE: 36°

POWER: 5.5W

LUMENS: 314lm

CBCP: 711cd

EFFICACY: 57lm/W



MODEL: ADDG25-LM07E330BWT


BEAM ANGLE: 36°

POWER: 8W

LUMENS: 452lm

CBCP: 1016cd

EFFICACY: 56lm/W



MODEL: ADDG25-LM04E530BWT


BEAM ANGLE: 50°

POWER: 5.5W

LUMENS: 330lm

CBCP: 468cd

EFFICACY: 60lm/W



MODEL: ADDG25-LM07E530BWT

BEAM ANGLE: 50°

POWER: 8W

LUMENS: 476lm

CBCP: 674cd

EFFICACY: 59lm/W

ELANA - MODEL: ADDG35
3" Square Narrow Side Recessed Downlight

WAC


PROJECT:

TYPE:

Product Image



Line Drawing



Product Description

The ELANA series of LED recessed downlights with square narrow edges are the perfect combination of downlighting and angle adjustment. Good anti-glare performance and color consistency control, with comfortable light effect, mainly suitable for indoor places such as hotels and clubs.

Product Features

- Body Material: Aluminum alloy die-casting
- Optical System: Lens+ Anti-glare reflector
Reflector surface treatment:
 - B Black
 - W White
 - S Black Mirror
 - T Black Step
 - H White Step
- Finish: Static electricity powder coating
- Adjustable Angle: Vertical 0°~25° , Acilic 0°~355°
- Accessories: As attached
- Certification: CCC
- IP Rating: IP20
- Insulation Level: Class II
- Operating Temperature: -20°C~40°C

Product Specifications

- Cut-out: 75*75mm
- Ceiling Thickness: 5mm~15mm
- Shielding Angle: 35°
- LED Type: COB
- Source Lm:
 - 2700K: 7W 758LM; 10W 1080LM; 13W 1404LM
 - 3000K: 7W 800LM; 10W 1150LM; 13W 1495LM
 - 3500K: 7W 835LM; 10W 1195LM; 13W 1554LM
 - 4000K: 7W 850LM; 10W 1210LM; 13W 1573LM
 - 5000K: 7W 860LM; 10W 1220LM; 13W 1586LM
- LED Lifetime: >36000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 2700K/ 3000K/3500K/4000K/5000K, Ra90
- SDCM: 3 SDCM (4000K 5SDCM)
- Input: 220V~240V AC / 50Hz
- Dimming: On-off / 0-10V /DALI
- Net Weight: 0.24Kg without packing

Order Model

Model	Size	Trim	LED	Driver	Beam	CCT	Reflector	Finish
ADDG Downlight Directional G series	3 3"	5 Rectangular Trim	LM07 COB 7W	E ON-OFF	1 15°	27 2700K	B Black	WT
			LM10 COB 10W	D 0-10V	2 24°	30 3000K	W White	White
			LM13 COB 13W	Dimming	3 36°	35 3500K	S Specular	BK
			LM13 COB 13W	N NO DRIVER	5 50°	41 4000K	T Black Step	Black
						50 5000K	H White Step	

Example: ADDG35-LM07E130SWT

Note: 15° and 24° have honeycomb by default, and there is no honeycomb at other angles

ELANA - MODEL: ADDG35
3" Square Narrow Side Recessed Downlight



PROJECT:

TYPE:









LENS-12-HCL-ELANA

Honeycomb



Note: 15° and 24° have honeycomb by default, and there is no honeycomb at other angles.

LIGHT DISTRIBUTION@3000K LUMINAIRE DATA


	MODEL: ADDG35-LM07E130BWT BEAM ANGLE: 15° POWER: 8W LUMENS: 344lm CBCP: 3767cd EFFICACY: 43lm/W		MODEL: ADDG35-LM10E130BWT BEAM ANGLE: 15° POWER: 11W LUMENS: 462lm CBCP: 5068cd EFFICACY: 42lm/W
	MODEL: ADDG35-LM13E130BWT BEAM ANGLE: 15° POWER: 15W LUMENS: 628lm CBCP: 6881cd EFFICACY: 41lm/W		MODEL: ADDG35-LM07E230BWT BEAM ANGLE: 24° POWER: 8W LUMENS: 593lm CBCP: 2303cd EFFICACY: 74lm/W
	MODEL: ADDG35-LM10E230BWT BEAM ANGLE: 24° POWER: 11W LUMENS: 798lm CBCP: 3098cd EFFICACY: 72lm/W		MODEL: ADDG35-LM13E230BWT BEAM ANGLE: 24° POWER: 15W LUMENS: 1083lm CBCP: 4206cd EFFICACY: 72lm/W
	MODEL: ADDG35-LM07E330BWT BEAM ANGLE: 36° POWER: 8W LUMENS: 593lm CBCP: 2303cd EFFICACY: 74lm/W		MODEL: ADDG35-LM10E330BWT BEAM ANGLE: 36° POWER: 11W LUMENS: 798lm CBCP: 3098cd EFFICACY: 72lm/W

ELANA - MODEL: ADDG35
3" Square Narrow Side Recessed Downlight




PROJECT:


TYPE:




MODEL:	ADDG35-LM10E330BWT
BEAM ANGLE:	36°
POWER:	15W
LUMENS:	1083lm
CBCP:	4206cd
EFFICACY:	72lm/W



MODEL:	ADDG35-LM07E530BWT
BEAM ANGLE:	50°
POWER:	8W
LUMENS:	553lm
CBCP:	735cd
EFFICACY:	69lm/W



MODEL:	ADDG35-LM10E530BWT
BEAM ANGLE:	50°
POWER:	11W
LUMENS:	744lm
CBCP:	988cd
EFFICACY:	67lm/W



MODEL:	ADDG35-LM13E530BWT
BEAM ANGLE:	50°
POWER:	15W
LUMENS:	1010lm
CBCP:	1342cd
EFFICACY:	67lm/W