

SILO FOCUS - MODEL: ATL15FLM

W Track Luminaires

WAC LIGHTING

Responsible Lighting®


Project Name:

Type:

Product Image



Line Drawing



Product Description

SILO Focus Series LED Track Lights are suitable for W 3-circuit track system. The design is exquisite, made of die-cast aluminum. Built-in non-strobe driver, COB light module, adjustable light angle continuously. Widely used in museums, art galleries, commercial spaces, hotels, retail and other places to provide accent lighting or ambient lighting.

Product Features

- **Body Material:** Aluminum alloy die-casting lamp body
- **Optical System:** Adjustable Focusing Lens
- **Finish:** Electrostatic Powder Coating, Black (BK), White (WT)
- **Adjustable Angle:** Horizontal 0°~355° adjustment; Vertical 0~90° adjustment
- **Accessory:** Add up to three optical accessories, up to one of each type at the same time
- **Certification:** CCC
- **IP Rating:** IP20
- **Insulation Class:** Class I
- **Operating Temperature:** -20°C~40°C

Product Specifications

- **LED Type:** COB
- **Power:** 6W or 12W Optional
- **Source Lm:** 2700K: 610lm (6W) / 1090lm (12W)
3000K: 670lm (6W) / 1200lm (12W)
4000K: 720lm (6W) / 1290lm (12W)
5000K: 770lm (6W) / 1380lm (12W)
- **LED Lifetime:** >50000h-L70 / B10-Ta25°C(LM-80/TM-21)
- **CCT/CRI:** 2700K / 3000K / 4000K / 5000K , >Ra90
- **SDCM:** 3 SDCM
- **Input:** 220V~240V AC / 50Hz
- **Dimming:** Built-in knob dimming (dimming range 10% ~100%), 1- 10V dimming (must do matching test with project site in advance)
- **Net Weight:** Approx. 0.5Kg, excluding packaging

Order Model

Model	LED	Dimming	Beam	CRI	CCT	Finish
ATL15F SILO Focus	LM06 COB 6W	O On-board	F 12~50°	9 90	27 2700K	WT White BK Black
	LM12 COB 12W	D 0-10V			30 3000K	
					40 4000K	
					50 5000K	
ATL15F	LM12	O	F	9	30	WT

Example: ATL15FLM12-OF930WT

WAC Lighting

www.waclighting.com (US)

www.waclighting.com.cn (China)

Headquarters

44 Harbor Park Drive • Port Washington, NY

Phone (516) 515.5000 • Fax (516) 515.5050

WAC Lighting(Shanghai)

14,Lane 299, Bi Sheng Road,Shanghai 201204

Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598

WAC Lighting reserves the right to periodically design and update products.2022-08-18

SILO FOCUS - MODEL: ATL15FLM

W Track Luminaires

WAC LIGHTING

Responsible Lighting®

Project Name:





Type:

Accessory

Accessory I	ALENS-16-BEL-C Striped Glass Lens		Soft Glass Lens ALENS-16-BSL-SW		Frosted Glass Lens ALENS-16-FR		Honeycomb Grid ALENS-16-HCL	
Accessory II	Anti-glare Tube ALENS-15-SNOOT 							
Accessory III	Four-leaf shades ATL-21-BD-SW 							

Note: Up to three optical accessories can be added, with a maximum of one of each type at the same time.

Light Curve Distribution @3000K Data

	MODEL: ATL15FLM06-OF930 BEAM ANGLE: 12° POWER: 8W LUMENS: 183lm CBCP: 2395cd EFFICACY: 23lm/W		MODEL: ATL15FLM06-OF930 BEAM ANGLE: 50° POWER: 8W LUMENS: 291lm CBCP: 424cd EFFICACY: 36lm/W
	MODEL: ATL15FLM12-OF930 BEAM ANGLE: 12° POWER: 14W LUMENS: 272lm CBCP: 3187cd EFFICACY: 19lm/W		MODEL: ATL15FLM12-OF930 BEAM ANGLE: 50° POWER: 14W LUMENS: 425lm CBCP: 616cd EFFICACY: 30lm/W

SILO FOCUS - MODEL: ATL16FLM

W Track Luminaires

WAC LIGHTING

Responsible Lighting®


Project Name:

Type:

Product Image



Line Drawing



Product Description

SILO Focus Series LED Track Lights are suitable for W 3-circuit track system. The design is exquisite, made of die-cast aluminum. Built-in non-strobe driver, COB light module, adjustable light angle continuously. Widely used in museums, art galleries, commercial spaces, hotels, retail and other places to provide accent lighting or ambient lighting.

Product Features

- **Body Material:** Aluminum alloy die-casting lamp body
- **Optical System:** Adjustable Focusing Lens
- **Finish:** Electrostatic Powder Coating, Black (BK), White (WT)
- **Adjustable Angle:** Horizontal 0°~355° adjustment; Vertical 0°~90° adjustment
- **Accessory:** Add up to three optical accessories, up to one of each type at the same time
- **Certification:** CCC
- **IP Rating:** IP20
- **Insulation Class:** Class I
- **Operating Temperature:** -20°C~40°C

Product Specifications

- **LED Type:** COB
- **Power:** 18W or 26W optional
- **Source Lm:** 2700K: 1550lm (18W) / 2270lm (26W)
3000K: 1700lm (18W) / 2500lm (26W)
4000K: 1820lm (18W) / 2670lm (26W)
5000K: 1950lm (18W) / 2870lm (26W)
- **LED Lifetime:** >50000h-L70 / B10-Ta25°C(LM-80/TM-21)
- **CCT/CRI:** 2700K / 3000K / 4000K / 5000K , >Ra90
- **SDCM:** 3 SDCM
- **Input:** 220V~240V AC / 50Hz
- **Dimming:** Built-in knob dimming (dimming range 10%~100%), DALI, 1-10V dimming (must be done in advance with the project site to match the test)
- **Net Weight:** Approx. 1.0Kg, excluding packaging

Order Model

Model	LED	Dimming	Beam	CRI	CCT	Finish
ATL16F SILO Focus	LM18 COB 18W	O On-board	F 12~50°	9 90	27 2700K	WT White BK Black
	LM26 COB 26W	A DALI			30 3000K	
		D 0-10V			40 4000K	
					50 5000K	
ATL16F	LM18	O	F	9	30	WT

Example: ATL16FLM18-OF930WT

WAC Lighting

www.waclighting.com (US)

www.waclighting.com.cn (China)

Headquarters

44 Harbor Park Drive • Port Washington, NY

Phone (516) 515.5000 • Fax (516) 515.5050

WAC Lighting(Shanghai)

14,Lane 299, Bi Sheng Road,Shanghai 201204

Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598

WAC Lighting reserves the right to periodically design and update products.2022-08-18

SILO FOCUS - MODEL: ATL16FLM

W Track Luminaires

WAC LIGHTING

Responsible Lighting®

Project Name:


Type:

Accessory

Accessory I	Striped Glass Lens ALENS-73-BEL-C 	Soft Glass Lens ALENS-73-BSL 	Frosted Glass Lens ALENS-73-FR 	Honeycomb Grid ALENS-73-HCL-C 
Accessory II	Anti-glare Tube ALENS-20-SNOOT 		Anti-glare Honeycomb ALENS-20-HCL 	
Accessory III	Four-leaf Shades ALENS-73-BD 			

Note: Up to three optical accessories can be added, with a maximum of one of each type at the same time.

Light Curve Distribution @3000K Data



MODEL: ATL16FLM18-OF930


BEAM ANGLE: 12°

POWER: 21W

LUMENS: 319lm

CBCP: 4670cd

EFFICACY: 15lm/W



MODEL: ATL16FLM18-OF930


BEAM ANGLE: 50°

POWER: 21W

LUMENS: 463lm

CBCP: 689cd

EFFICACY: 22lm/W



MODEL: ATL16FLM26-OF930


BEAM ANGLE: 12°

POWER: 30W

LUMENS: 439lm

CBCP: 5859cd

EFFICACY: 15lm/W



MODEL: ATL16FLM26-OF930

BEAM ANGLE: 50°

POWER: 30W

LUMENS: 639lm

CBCP: 952cd

EFFICACY: 21lm/W

WAC Lighting

www.waclighting.com (US)

www.waclighting.com.cn (China)

Headquarters

44 Harbor Park Drive • Port Washington, NY

Phone (516) 515.5000 • Fax (516) 515.5050

WAC Lighting(Shanghai)

14,Lane 299, Bi Sheng Road,Shanghai 201204

Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598

WAC Lighting reserves the right to periodically design and update products.2022-08-18

SILO FOCUS - MODEL: ATL17FLM

W Track Luminaires

WAC LIGHTING

Responsible Lighting®


Project Name:

Type:

Product Image



Line Drawing



Product Description

SILO Focus Series LED Track Lights are suitable for W 3-circuit track system. The design is exquisite, made of die-cast aluminum. Built-in non-strobe driver, COB light module, adjustable light angle continuously. Widely used in museums, art galleries, commercial spaces, hotels, retail and other places to provide accent lighting or ambient lighting.

Product Features

- **Body Material:** Aluminum alloy die-casting lamp body
- **Optical System:** Adjustable Focusing Lens
- **Finish:** Electrostatic Powder Coating, Black (BK), White (WT)
- **Adjustable Angle:** Horizontal 0°~355° adjustment; Vertical 0~90° adjustment
- **Accessory:** Add up to three optical accessories, up to one of each type at the same time
- **Certification:** CCC
- **IP Rating:** IP20
- **Insulation Class:** Class I
- **Operating Temperature:** -20°C~40°C

Product Specifications

- **LED Type:** COB
- **Power:** 34W
- **Source Lm:** 3280lm (2700K) / 3600lm (3000K)
3880lm (4000K) / 4140lm (5000K)
- **LED Lifetime:** >50000h-L70 / B10-Ta25°C(LM-80/TM-21)
- **CCT/CRI:** 2700K / 3000K / 4000K / 5000K , >Ra90
- **SDCM:** 3 SDCM
- **Input:** 220V~240V AC / 50Hz
- **Dimming:** Built-in knob dimming (dimming range 10%~100%), DALI, 1 - 10V dimming (must be done in advance with the project site to match the test)
- **Net Weight:** Approx. 1.4Kg, excluding packaging

Order Model

Model	LED	Dimming	Beam	CRI	CCT	Finish
ATL17F SILO Focus	LM34 COB 34W	O On-board A DALI D 0-10V	F 12~50°	9 90	27 2700K 30 3000K 40 4000K 50 5000K	WT White BK Black
ATL17F	LM34	O	F	9	30	WT

Example: ATL17FLM34-OF930WT

WAC Lighting

www.waclighting.com (US)

www.waclighting.com.cn (China)

Headquarters

44 Harbor Park Drive • Port Washington, NY

Phone (516) 515.5000 • Fax (516) 515.5050

WAC Lighting(Shanghai)

14,Lane 299, Bi Sheng Road,Shanghai 201204

Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598

WAC Lighting reserves the right to periodically design and update products.2022-08-18

SILO FOCUS - MODEL: ATL17FLM

W Track Luminaires

WAC LIGHTING

Responsible Lighting®

Project Name:


Type:

Accessory


Accessory I	Striped Glass Lens ALENS-73-BEL-C 	Soft Glass Lens ALENS-73-BSL 	Frosted Glass Lens ALENS-73-FR 	Honeycomb Grid ALENS-73-HCL-C 
Accessory II	Anti-glare Tube ALENS-20-SNOOT 		Anti-galre Honeycomb ALENS-20-HCL 	
Accessory III	Four-leaf Shades ATL-22-BD-SW 			

Note: Up to three optical accessories can be added, with a maximum of one of each type at the same time.

Light Curve Distribution @3000K Data



MODEL:	ATL17FLM34-OF930
BEAM ANGLE:	12°
POWER:	38W
LUMENS:	564lm
CBCP:	6780cd
EFFICACY:	15lm/W



MODEL:	ATL17FLM34-OF930
BEAM ANGLE:	50°
POWER:	38W
LUMENS:	813lm
CBCP:	1205cd
EFFICACY:	21lm/W