

OCULARC FOCUS - MODEL: APL5F4

Vertically Mounted Luminaire

WAC


PROJECT:

TYPE:

Product Image



Line Drawing



Product Description

The Ocularc Focus series pole mounted lamps have a flexible design and small size; Adopting WAC's leading SUBROSA dimming technology with a built-in 30 ° antiglare angle, achieving the ultimate antiglare effect; The beam angle can be infinitely adjusted to meet the needs of different application environments, and is widely used in exhibition cabinet spaces in museums and art galleries.

Product Features

- Body Material: Aluminum alloy die-casting, Glass optical devices
- Optical System: Lens+ SUBOROSA optical system
- Finish: Liquid paint, black (BK)
- Adjustable Angle: Horizontal 0°~360° tilt ; Vertical 0~90°tilt
- Accessories: /
- Certification: CQC
- IP Rating: IP20
- Insulation Level: Class III
- Operating Temperature: -20°C~40°C

Product Specifications

- Cut-out: Ø13, Ceiling Thickness 1mm~30mm
- Lamp height: 20-400mm adjustable ("L" in the line drawing)
- LED Type: HP LED
- LED Power: 1W
- Source Lm: 3000K 105LM; 4000K 110LM
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 2700K/3000K/3500K/4000K/5000K , Ra90
- SDCM: 3 SDCM (4000K 5SDCM)
- Input: constant current 350mA max (3VDC)
- Dimming: MTB power divider (1W) can be matched, See its specifications (order separately)
- Net Weight: 0.1Kg without packing

OCULARC FOCUS - MODEL: APL5F4

Vertically Mounted Luminaire

WAC

PROJECT:

TYPE:

Order Model

Model	LED	Dimming	Beam	CRI	CCT	Finish
APL45F Ocularc Focus	LD01 LED 1W	M MTB Driver N Single Wire	F 10-40°	9 90 A 97	30 3000K 40 4000K	BK Black
APL45F	LD01	M	F	9	30	BK

Example : APL45FLD01-MF930BK

Accessory

AMBT-CABLE-1000-BK

PL45FLD01-M Dedicated extension cable: used between MTB power splitter and PL45FLD01-M series display

cabinet lighting fixtures, with a total length of 1m and quick connect plugs at both ends



Notes: APL45FLD01-M The length of the input wire for the original lighting fixture is about 0.5 meters.

The dedicated MTB power splitter and extension cable need to be ordered separately. (<http://www.waclighting.com.cn/products/detail/3147>).

A4LD-350MA10D-LF-C


Special electrical appliances:

Input 220V~240V AC / 50Hz,

Output 350mA, 6-30V;

Supports 0-10V dimming and can drive 2-8 lighting fixtures (in series)


Dimensions (L * W * H): 121 * 41 * 22, mm




Note: The length of the input wire for the original APL45FLD01-N lamp is approximately 0.3 meters. APL45FLD01-N special electrical appliances need to be ordered separately, excluding cables.

LIGHT DISTRIBUTION@3000K LUMINAIRE DATA

MODEL:	APL45FLD01-MF930(min)
BEAM ANGLE:	10°
POWER:	1W (Excluding electrical appliances)
LUMENS:	14lm
CBCP:	340cd
EFFICACY:	14lm/W



MODEL:	APL45FLD01-MF930 (max)
BEAM ANGLE:	10°
POWER:	1W (Excluding electrical appliances)
LUMENS:	37lm
CBCP:	78cd
EFFICACY:	37lm/W



OCULARC FOCUS - MODEL: APL6F4

Vertically Mounted Luminaire

WAC


PROJECT:

TYPE:

Product Image



Line Drawing



Product Description

The Ocularc Focus series pole mounted lamps have a flexible design and small size; Adopting WAC's leading SUBROSA dimming technology with a built-in 30 ° antiglare angle, achieving the ultimate antiglare effect; The beam angle can be infinitely adjusted to meet the needs of different application environments, and is widely used in exhibition cabinet spaces in museums and art galleries.

Product Features

- Body Material: Aluminum alloy die-casting, Glass optical devices
- Optical System: Lens+ SUBOROSA optical system
- Finish: Liquid paint, black (BK)
- Adjustable Angle: Horizontal 0°~360° tilt ; Vertical 0~90° tilt
- Accessories: /
- Certification: CQC
- IP Rating: IP20
- Insulation Level: Class III
- Operating Temperature: -20°C~40°C

Product Specifications

- Cut-out: Ø13, Ceiling Thickness 1mm~30mm
- Lamp height: 20-400mm adjustable ("L" in the line drawing)
- LED Type: HP LED
- LED Power: 3W
- Source Lm: 3000K 250LM; 4000K 265LM
- LED Lifetime: >50000h-L70
- CCT/CRI: /B10-Ta25°C(LM-80/TM-21) 2700K/3000K/3500K/4000K/5000K, Ra90
- SDCM: 3 SDCM (4000K 5SDCM)
- Input: constant current 1050mA max (3VDC)
- Dimming: MTB power divider (3W) can be matched, See its specifications (order separately)
- Net Weight: 0.1Kg without packing

OCULARC FOCUS - MODEL: APL6F4

Vertically Mounted Luminaire

WAC

PROJECT:

TYPE:

Order Model

Model	LED	Dimming	Beam	CRI	CCT	Finish
APL46F Ocularc Focus	LD03 LED 3W	M MTB Driver N Single Wire	F 10-40° F 8-40°	9 90 A 97	30 3000K 40 4000K	BK Black
APL46F	LD03	M	F	9	30	BK

Example : APL45FLD01-M-F930BK

Accessory


AMTB-CABLE-1000-BK

APL46FLD03-M Dedicated extension cable: used between MTB power splitter and APL46FLD03-M series display cabinet lighting fixtures, with a total length of 1m and quick connect plugs at both ends




Notes: APL46FLD03-M The length of the input wire for the original lighting fixture is about 0.5 meters. The dedicated MTB power splitter and extension cable need to be ordered separately. (<http://www.waclighting.com.cn/products/detail/3147>).

LIGHT DISTRIBUTION@3000K LUMINAIRE DATA



MODEL:	APL46FLD03-MF930(min)
BEAM ANGLE:	6°
POWER:	3W (Excluding electrical appliances)
LUMENS:	44lm
CBCP:	2069cd
EFFICACY:	15lm/W



MODEL:	APL46FLD03-MF930 (max)4
BEAM ANGLE:	40°
POWER:	3W (Excluding electrical appliances)
LUMENS:	138lm
CBCP:	348cd
EFFICACY:	46lm/W