

AQUASTAR - MODEL: AEU1S

Underwater Luminaires



PROJECT:

TYPE:

Product Image

Line Drawing

Product Description

Aquastar series underwater floodlights , Fully cast copper lamp body , Faster and more stable heat dissipation , Durable and sturdy material. Install in a horseshoe shape, Exquisite and meticulous appearance and structural design, Excellent optical performance, Suitable for fountain, swimming pool, and seaside functional lighting.

Product Features

- Body Material: Copper lamp body
- Optical System: Lens
- Finish: /
- Adjustable Angle: -30~+90°
- Accessories: /
- Certification: /
- IP Rating: IP68
- Insulation Level: Class III
- Operating Temperature: -20°C~50°C

Product Specifications

- LED Type: Hight Power LED
- Light Power 6.6W (Max)
- Source Lm: 3000K 560lm
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 3000K,4000K,6000K ,Ra80;RGB,Blue 2700K-C
- SDCM: 3 SDCM
- Input: 12V DC
- Dimming: ON-OFF /DMX512
- Net Weight: 2.7Kg without packing

Order Model

Model	Power (W)	LED (quantity)	Max Lumens	Control Systems	Beam	CCT	Finish
AEU1S-07	7(Max)	3	517	ET ON-OFF 12V DC Power Supply MT DMX512 Dimming 12V DC Power Supply	S 8° 1 15° 2 20° 4 40°	30 3000K 40 4000K 60 6000K FC RGB B Blue	NB Natural Brass

Example: AEU1S-07ET-S30NB

AQUASTAR - MODEL: AEU1S

Underwater Luminaires



PROJECT:

TYPE:

Model	Power (W)	LED (quantity)	Max Lumens	Control Systems	Beam	CCT	Finish
AEU1S-07	7(Max)	1	160	MT DMX512 Dimming 12V DC Power Supply	1 15° 2 25° 4 35°	F40 RGBW(4000K) F60RGBW(6000K)	NB Natural Brass

Example: AEU1S-07MT1F40NB

ACCESSORY

LIGHT DISTRIBUTION@3000K LUMINAIRE DATA

	<div>MODEL: AEU1S-07ETS30NB</div> <div>BEAM ANGLE: 9.5°</div> <div>POWER: 7.9W</div> <div>LUMENS: 480.9lm</div> <div>CBCP: /</div> <div>EFFICACY: 61.1lm/W</div>		<div>MODEL: AEU1S-07ET130NB</div> <div>BEAM ANGLE: 14.3°</div> <div>POWER: 7.9W</div> <div>LUMENS: 516.9lm</div> <div>CBCP: /</div> <div>EFFICACY: 65.4lm/W</div>
	<div>MODEL: AEU1S-07ET230NB</div> <div>BEAM ANGLE: 19.8°</div> <div>POWER: 7.9W</div> <div>LUMENS: 512.3lm</div> <div>CBCP: /</div> <div>EFFICACY: 64.8lm/W</div>		<div>MODEL: AEU1S-07ET430NB</div> <div>BEAM ANGLE: 36.9°</div> <div>POWER: 7.9W</div> <div>LUMENS: 472lm</div> <div>CBCP: /</div> <div>EFFICACY: 59.8lm/W</div>